



DRY-LOCK METRIC FITTINGS 24°  
INSERTI METRICI 24° DRY-LOCK

## IMES

CES - DRY-LOCK METRIC MALE, 24° CONE, HEAVY

CES - DRY-LOCK MASCHIO METRICO, CONO 24°, SERIE PESANTE

Thread - *Filetto*: METRIC

Norme - *Norma*: DIN 3861

Notes

\* WHILE STOCKS LAST

Note

\* ARTICOLO IN ESAURIMENTO

| Code Article<br><i>Codice Articolo</i> | Thread<br><i>Filetto</i> | Hose<br><i>Tubo</i> | Standpipe<br><i>Codolo</i> | Dimensions (mm)<br><i>Dimensioni (mm)</i> |    |      |      |    |
|----------------------------------------|--------------------------|---------------------|----------------------------|-------------------------------------------|----|------|------|----|
|                                        | F                        | Inch/Pollici        | DN (mm)                    | mm                                        | CH | A    | P    | L  |
| IMES2012                               | M30X2                    | 3/4                 | 19                         | 20                                        | 30 | 34,1 | 10,5 | 16 |
| IMES2512                               | M36X2                    | 3/4                 | 19                         | 25                                        | 36 | 37,1 | 12   | 18 |
| IMES2516                               | M36X2                    | 1"                  | 25                         | 25                                        | 36 | 38   | 12   | 18 |
| IMES3016                               | M42X2                    | 1"                  | 25                         | 30                                        | 46 | 41   | 13,5 | 20 |
| IMES3020*                              | M42X2                    | 1"1/4               | 32                         | 30                                        | 46 | 38   | 14   | 20 |
| IMES3820                               | M52X2                    | 1"1/4               | 32                         | 38                                        | 55 | 45,5 | 16,5 | 22 |