

SPIRAL HOSES FOR VERY HIGH PRESSURE
TUBI SPIRALATI PRESSIONI ELEVATE

TUBO15

HOSE 4 - 6 SPIRALS R15
TUBO 4 - 6 SPIRALI R15

Norme - Norma: SAE 100 R15



Notes

TUBE:
SYNTHETIC RUBBER, RESISTANT AGAINST
HYDRAULIC FLUIDS
REINFORCEMENT:
FOUR SPIRAL LAYERS DN 19 - DN 25; SIX
SPIRAL LAYERS DN 32 - DN 38 OF HIGH
TENSILE STEEL WIRE
COVER:
ABRASION AND OZONE RESISTANT
SYNTHETIC RUBBER MSHA APPROVED.
TEMPERATURE RANGE (FLUID):
FROM -40 °C TO 120°C

Note

SOTTOSTRATO:
GOMMA SINTETICA RESISTENTE AGLI OLII
RINFORZO:
QUATTRO SPIRALI DN 19 - DN 25; SEI SPIRALI
DN 32 - DN 38 DI ACCIAIO AD ALTA TENACITÀ
COPERTURA:
GOMMA SINTETICA RESISTENTE
ALL'ABRASIONE, ALL'OZONO E AGLI AGENTI
ATMOSFERICI; OMOLOGATO MSHA
RANGE DELLE TEMPERATURE (FLUIDO):
DA -40°C A +120°C

Code Article Codice Articolo	Inside ø ø Interno		ø Braid ø Treccia	ø Out ø Est	W.P. Esercizio		Burst Scoppio	Radius Raggio	Weight Peso	Ferrule Boccola
	Inch/Poll	DN (mm)	mm	mm	bar	psi	bar	mm	Kg/mt	
TUBO1215	3/4	19	28,3	31,9	420	6090	1680	265	1,43	B4I12-BDR12
TUBO1615	1'	25	35,4	38,7	420	6090	1680	330	2,16	B4I16-BDR16
TUBO2015	1' 1/4	31	48	51,3	420	6090	1680	445	2,96	B1320-BDS20
TUBO2415	1' 1/2	38	56,3	59,6	420	6090	1680	530	5,1	B1324-BDS24